

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 1 026 341 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
09.08.2000 Bulletin 2000/32

(51) Int Cl.<sup>7</sup>: E04F 15/04

(21) Application number: 00201514.7

(22) Date of filing: 07.06.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
Designated Extension States:  
AL LT LV RO SI

(72) Inventor: The designation of the inventor has not yet been filed

(74) Representative: Donné, Eddy  
Bureau M.F.J. Bockstael nv  
Arenbergstraat 13  
2000 Antwerpen (BE)

(30) Priority: 11.06.1996 BE 9600527  
15.04.1997 BE 9700344

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
97928169.8 / 0 843 763

### Remarks:

This application was filed on 27 - 04 - 2000 as a divisional application to the application mentioned under INID code 62.


(71) Applicant: Unilin Beheer B.V.  
2913 LV Nieuwerkerk aan de IJssel (NL)

(54) Floor covering, consisting of hard floor panels and method for manufacturing such floor panels

(57) Floor covering, consisting of hard floor panels (1) which, at least at the edges of two opposite sides (2-3, 26-27), are provided with coupling parts (4-5, 28-29), co-operating with each other, substantially in the form of a tongue (9-31) and a groove (10-32), whereby the coupling parts are provided with integrated mechanical locking means (6) made in one piece with the panels (1) which prevent the drifting apart of two coupled floor panels (1) into a direction (R) perpendicular to the relat-

ed edges (2-3, 26-27) and parallel to the underside (7) of the coupled floor panels (1), characterized in that the coupling parts (4-5, 28-29) are provided with means which, in the engaged condition of two or more of such floor panels (1), exert a tension force upon each other which forces the floor panels (1) towards each other, said means comprising an elastically bendable portion which, in the engaged condition, is at least partially bent and in this manner provides the aforementioned tension force.

Fig. 1



EP 1 026 341 A2

## Description

[0001] This invention relates to a floor covering, consisting of hard floor panels, as well as to a method for manufacturing such floor panels.

[0002] In first instance, the invention is intended for so-called laminated floors, but generally it can also be applied for other kinds of floor covering, consisting of hard floor panels, such as veneer parquet, prefabricated parquet, or other floor panels which can be compared to laminated floor.

[0003] It is known that such floor panels can be applied in various ways.

[0004] According to a first possibility, the floor panels are attached at the underlying floor, either by glueing or by nailing them on. This technique has as a disadvantage that it is rather complicated and that subsequent changes can only be made by breaking out the floor panels.

[0005] According to a second possibility, the floor panels are installed loosely onto the underground, whereby the floor panels mutually match into each other by means of a tongue and groove coupling, whereby mostly they are glued together in the tongue and groove, too. The floor obtained in this manner, also called a floating parquet flooring, has as an advantage that it is easy to install and that the complete floor surface can move which often is convenient in order to receive possible expansion and shrinkage phenomena.

[0006] A disadvantage with a floor covering of the above-mentioned type, above all, if the floor panels are installed loosely onto the underground, consists in that during the expansion of the floor and its subsequent shrinkage, the floor panels themselves can drift apart, as a result of which undesired joints can be formed, for example, if the glue connection breaks.

[0007] In order to remedy this disadvantage, techniques have already been thought of whereby connection elements made of metal are provided between the single floor panels in order to keep them together. Such connection elements, however, are rather expensive in manufacturing them and, furthermore, their provision or the installation thereof is a time-consuming occupation.

[0008] Examples of embodiments which apply such metal connection elements are described, among others, in the documents WO 94/26999 and WO 93/13280.

[0009] Furthermore, couplings are known which allow to snap floor parts into each other, a.o. from the documents WO 94/1628, WO 96/27719 and WO 96/27721. The snapping-together effect obtained with these forms of embodiment, however, does not guarantee a 100-percent optimum counteraction against the development of gaps between the floor panels, more particularly, because in fact well-defined plays have to be provided in order to be sure that the snapping-together is possible.

[0010] From GB 424.057, a coupling for parquetry parts is known which, in consideration of the nature of

the coupling, only is appropriate for massive wooden parquetry.

[0011] Furthermore, there are also couplings for panels known from the documents GB 2.117.813, GB 2.256.023 and DE 3.544.845. These couplings, however, are not appropriate for connecting floor panels.

[0012] The invention aims at an improved floor covering of the aforementioned type, the floor panels of which can be coupled to each other in an optimum manner and/or the floor panels of which can be manufactured in a smooth manner, and whereby preferably one or more of the aforementioned disadvantages are excluded.

[0013] The invention also aims at a floor covering which shows the advantage that no mistake during installing, such as gaps and such, can be created.

[0014] Furthermore, the invention also aims at a floor covering whereby the subsequent development of gaps is excluded or at least counteracted in an optimum manner, whereby also the possibility of the penetration of dirt and humidity is minimized.

[0015] To this aim, the invention relates to a floor covering, consisting of hard floor panels which, at least at the edges of two opposite sides, are provided with coupling parts, co-operating with each other, substantially in the form of a tongue and a groove, whereby the coupling parts are provided with integrated mechanical locking means made in one piece with the panels which prevent the drifting apart of two coupled floor panels into a direction perpendicular to the related edges and parallel to the underside of the coupled floor panels, characterized in that the coupling parts are provided with means which, in the engaged condition of two or more of such floor panels, exert a tension force upon each other which forces the floor panels towards each other, said means comprising an elastically bendable portion which, in the engaged condition, is at least partially bent out and in this manner provides the aforementioned tension force.

[0016] As a result of this is effected that not only during installing the formation of gaps is counteracted, but also in a later stage the development of gaps, as a result of which causes whatsoever, is counteracted.

[0017] Due to the fact that the coupling parts provide for an interlocking free from play, as well due to the fact that these coupling parts are manufactured in one piece, from the basic material of the floor panels, a perfect connection between adjacent floor panels can always be guaranteed, even with repeated expansion and shrinkage of the floor surface.

[0018] According to a preferred form of embodiment, the floor covering is characterized in that the lower lip which limits the lower side of the groove, extends beyond the upper lip; that the locking means are formed at least of a portion which inwardly slopes downward; and that, preferably, this portion, at least partially, is located in the portion of the lower lip which extends beyond the upper lip. The advantages of these features will appear from the further description.

[0019] According to a preferred form of embodiment, the floor panels consist of elongated panels and the coupling parts described above are applied along the longitudinal sides of these panels.

[0020] According to a particular form of embodiment, coupling parts are provided at the other two sides, too, either of another construction than described above or not.

[0021] In the most preferred form of embodiment, for the basic material use shall be made of the aforementioned product, which, as said, is ground and, by means of a binding agent, composed to a single compound. More particularly, for the core use shall be made of finely-ground wood which preferably is glued, more particularly, watertight glued. Still more particularly, for the core use shall be made of so-called HDF board (High Density Fibreboard) or MDF (Medium Density Fibreboard).

[0022] The fact that the invention is applied to floor panels the basic material of which consists of the material described above, offers the advantage that with the processing of this material, very smooth surfaces are obtained whereby very precise couplings can be realized, which, in first instance, is important in the case of a snap-together connection and/or turning connection free from play. Also, very special forms of coupling parts can be manufactured in a very simple manner because the aforementioned kinds of material can be processed particularly easy.

[0023] The surfaces obtained with HDF and MDF also have the advantage that the floor panels mutually can fluently be shifted alongside each other in interlocked condition, even when engaged with a tensioning force.

[0024] The inventor also found out that the aforementioned materials, in particular HDF and MDF, show ideal features in order to realize a connection, such as mentioned above, as these materials show the right features in respect to elastic deformation in order to, on one hand, realize a snap-together effect, and, on the other hand, receive expansion and shrinkage forces in an elastic manner, whereby it is avoided that the floor panels come unlocked or are damaged in an irreparable manner.

[0025] In the case that for the core use is made of a material based on synthetic material, to this end solid synthetic material can be used as well as a mixture of synthetic materials, eventually composed of recycled materials.

[0026] Other features of the floor covering, as well as of the floor panels for realizing such floor covering, providing in a further optimization, can be derived from the enclosed subclaims 2 to 21 and 29.

[0027] The floor covering preferably is formed by joining the floor panels into each other free of glue. Hereby, the connections are of such nature that the floor panels can be disassembled without being damaged, such that, for example, when moving, they can be taken along in order to be placed again. It is, however, clear that a glue-

ing between tongue and groove is not excluded.

[0028] The joining together of the panels is preferably realized according to one of the methods described in the enclosed subclaims 22 to 28.

5 [0029] The invention, of course, also relates to floor panels which allow the realization of the aforementioned floor covering.

[0030] The invention also relates to a method for the manufacturing of the aforementioned floor panels which shows the advantage that the tongues and/or grooves, including the corresponding locking means, can be provided at the floor panels at high production speeds without problems. More particularly, it aims at a method which allows that the rather complicated forms of the tongue and the groove of the aforementioned floor panels can be realized, such that the use of small milling cutters, for example finger cutters, with diameters smaller than the depth of the tongue or groove can be excluded.

20 [0031] To this aim, this method shows the characteristic that the tongue and/or groove is realized by means of a milling process with at least two subsequent milling cycles by means of milling cutters which are positioned in different angles in respect to the related floor panel. During each of the aforementioned milling cycles, preferably substantially the final form of one flank, either of the tongue or of the groove, is realized.

25 [0032] For the aforementioned two milling cycles, thus, milling cutters are used which extend outside the groove, respectively the tongue. More particularly the diameters of these milling cutters shall at least be 5 times and even better 20 times larger than the thickness of the floor panels.

[0033] The use of milling cutters showing the aforementioned diameters has as an advantage that the normal production speeds can be maintained which are also applied during milling of a classical straight tongue and groove. There is also the advantage obtained that the installation of such milling cutters induce only minor or no additional costs because such milling cutters can be placed directly upon a motor shaft and/or the usual machines can be used.

40 [0034] With the intention of better showing the characteristics according to the invention, in the following, as an example without any limitative character, several preferred forms of embodiment are described, with reference to the accompanying drawings, wherein:

50 figure 1 represents a floor panel of a floor covering according to the invention;

figure 2, on a larger scale, represents a cross-section according to line II-II in figure 1;

figures 3 and 4 represent how two floor panels with coupling parts according to figure 2 match into each other;

55 figure 5, on a larger scale, represents a cross-section according to line V-V in figure 1;

figures 6 and 7 represent how two floor panels with

coupling parts according to figure 5 match into each other;

figures 8 to 11 represent a number of variants of coupling parts of floor panels according to the invention;

figure 12 schematically represents how the floor parts can be provided with coupling parts;

figure 13 represents a cross-section according to line XIII-XIII in figure 12;

figures 14 to 21, on a larger scale and in cross-section, represent the penetration of the milling cutters which are indicated in figure 12 with arrows F14 to F21;

figure 22 represents a floor panel according to the invention;

figure 23, on a larger scale, represents the coupling of two floor panels of figure 22;

figures 24 and 25 represent two manners of coupling floor panels according to figure 22 to each other.

**[0035]** The invention relates to a floor covering which is composed of hard floor panels 1, for example, such as shown in figure 1.

**[0036]** These floor panels 1 can be of various shape, for example, rectangular or square, or of any other shape.

**[0037]** In the most preferred form of embodiment, they shall be manufactured in an elongated form, such as shown in figure 1, for example, with a length of 1 to 2 meters. The thickness, however, can also vary, but is preferably 0,5 to 1,5 cm, and more particularly 0,8 cm.

**[0038]** Each floor panel 1 is, at least at the edges of two opposite sides 2-3, provided with coupling parts 4-5 which allow that two adjacent floor panels 1 can be coupled to each other.

**[0039]** According to the invention, the coupling parts 4-5, as represented in the figures 2 to 4, are provided with integrated mechanical locking parts 6 which prevent the drifting apart of two coupled floor panels 1 into a direction D perpendicular to the respective sides 2-3 and parallel to the underside 7 of the coupled floor panels 1; the coupling parts 4-5 and the locking means 6 are realized in one piece with the core 8 of the floor panels 1; the coupling parts 4-5 have such a shape that two subsequent floor panels 1 can be engaged into each other exclusively by snapping-together and/or turning, whereby each subsequent floor panel 1 can be laterally inserted into the previous; and the coupling parts 4-5 preferably provide in an interlocking free from play according to all directions in the plane which is situated perpendicular to the aforementioned edges.

**[0040]** In the case of floor panels 1 with an elongated shape, as represented in figure 1, the respective coupling parts 4-5 are situated at the longitudinal sides 2-3.

**[0041]** The coupling parts 4-5 can be realized in various forms, although the basic forms thereof will always be formed by a tongue 9 and a groove 10.

**[0042]** In the form of embodiment of figures 2 to 4, the related floor panel 1 is provided with coupling parts 4-5 and locking means 6 which allow to mutually engage two floor panels 1 by means of a turning movement, without the occurrence of any snap-together effect.

**[0043]** In the represented example, the locking means 9 consist of a first locking element 11, formed by a protrusion with a bent round shape at the lower side 12 of the tongue 9, and a second locking element 13, formed by a recess with a bent hollow shape in the lower wall 14 of the groove 10.

**[0044]** The locking elements 11-13 provide for that two floor panels 1 which are coupled to each other can not perform a lateral movement in the horizontal plane in respect to each other.

**[0045]** In order to obtain that two floor panels 1 can be inserted into each other by means of a turning movement, the curvatures preferably are circle-shaped. The bottom side 12 has a curvature with a radius R1, the center of which coincides with the related upper edge 15 of the floor panel 1, whereas the lower wall 14 shows a curvature with a radius R2 which is equal to the radius R1, but whereby its center coincides with the related upper edge 16. Radii R1 and R2 may also be applied which are larger or smaller than the distance to the upper edge 15, 16 respectively, and/or which differ from each other in size.

**[0046]** The upper side 17 of the tongue 9 and the upper wall 18 of the groove 10 are preferably flat and preferably are situated in the horizontal plane.

**[0047]** The front sides 19 and 20 of the tongue 9 and the groove 10 of two interlocked floor panels 1 preferably do not fit closely against each other, such, that in between an intermediate space 21 is created into which possible dust remainders or such can be pushed away by means of the tongue 9.

**[0048]** The tongue 9 and the groove 10 preferably have shapes which are complementary to each other, such that the tongue 9 in the engaged condition of two floor panels 1 precisely sits against the upper wall 18 and the lower wall 14 of the groove 10, whereby a pressure P, executed onto the upper lip 22, is received not only by this lip 22, but by the complete structure, because this pressure can be transmitted through the tongue 9 and the lower lip 23.

**[0049]** It is, however, clear that a number of minor deviations to these complementary forms can occur which, anyhow, have no or almost no effect upon the receipt and transmission of pressure forces. For example, a chamfer 24 and a recess 25 can be provided, as represented in figures 2 to 4, as a result of which is obtained that the subsequent floor panels 1 can easily be pushed into each other, such that no possible ridges or such render the good insertion difficult.

**[0050]** As represented in the figures 5 to 7, the floor panels 1 according to the invention can also, along the sides 26-27 which are at a right angle to the sides 2-3, be provided with coupling parts 28-29 which have lock-

ing means 30, too. The coupling parts 28-29 are preferably also realized in the shape of a tongue 31 and a groove 32. Hereby, the locking means 30 do not have to be of the same nature as the locking means 6.

[0051] Preferably, at the sides 26-27 locking means are applied which allow for an engagement and interlocking by means of a translation movement T only, as represented in figures 6 and 7. To this aim, the locking means 30 consist of a snap-together connection with locking elements 33 and 34 which grip behind each other.

[0052] As represented in figures 5 to 7, the locking element 33 preferably consists of a protrusion of the lower side 35 of the tongue 31 which can take place in a recess 36 in the lower wall 37 of the groove 32. The locking element 34 is formed by the upward directed part which limits the recess 36.

[0053] In this case, the locking elements 33-34 have contact planes 38-39 which are parallel to each other and preferably extend in an inclined manner, according to a direction which simplifies the snapping-together. The tangent line L which is determined by the contact planes 38-39, hereby forms an angle A with the underside 7 which is smaller than  $90^\circ$ .

[0054] The locking elements 33-34 preferably are provided with inclined portions 40 and 41 which, when engaging two floor panels 1, cooperate with each other in such a manner that the locking elements 33-34 can easily be pushed over each other until they grip behind each other by means of a snap-together effect.

[0055] The thickness W1 of the tongue 31 preferably is equal to the width W of the groove 32, such that the upper lip 42, when exerting a pressure P, is supported by the tongue 31 which, in its turn, then is supported by the lower lip 43.

[0056] Analogous to the chamfer 24 and recess 25, a recess 44 and a chamfer 45 are provided also at the edges 28-29.

[0057] It is noted that such a snap-together coupling can also be applied at the edges 2-3. Hereby, this can be a snap-together coupling analogous to these of figures 5 to 7, but this can also be a snap-together coupling whereby other forms of coupling parts are applied, for example, such as represented in figures 8 and 9. Contrary to the locking elements 33-34 which consist of rather local protrusions, in the forms of embodiment of figures 8 and 9 use is made of locking elements 46-47 which, in comparison to the total width B of the coupling, extend over a rather large distance.

[0058] In this case, the locking elements 46-47 are also provided at the lower side 12 of the tongue 9 and the lower wall 14 of the groove 10.

[0059] According to figure 8, the locking elements 46-47 have contact surfaces 48-49 which are at an angle with the plane of the floor panel 1. Hereby, a coupling is obtained which is interlocked in a particularly fixed manner.

[0060] As represented in figure 9, the locking ele-

ments 46-47 possibly can be realized in such a manner that substantially only a linear contact is obtained, for example, because the contact surfaces directed towards each other are realized with different curvatures.

[0061] The surfaces, directed towards each other, of the locking elements 46-47 hereby consist of bent surfaces. The tangent line L forms an angle A which is smaller than  $90^\circ$ , and even better is smaller than  $70^\circ$ .

[0062] Hereby, the locking element 46 preferably has two portions with a different curvature, on one hand, a portion 50 with a strong curvature and, on the other hand, a portion 51 with a weak curvature. The portion 50 with the strong curvature provides for the formation of a firm coupling. The portion 51 with the weak curvature allows that the coupling parts 4-5 can be brought into each other easily. The intermediate space S forms a chamber which offers space for dust and similar which, when engaging two floor panels 1, gets there eventually.

[0063] In the case of a snap-together connection, for example, a connection, such as represented in figures 7 to 9, preferably always the tongue 9-31 has a shape, thickening towards below, which can cooperate with a widened portion in the groove 10.

[0064] In figure 10, a variant is represented whereby at least at the height of the upper edges 15-16, a sealing material 52 is provided, as a result of which a watertight sealing can be guaranteed. This sealing material 52 may consist of a strip or covering which is provided previously at the floor panel 1, either at one or both upper edges 15-16.

[0065] In figure 11, a further variant is represented, whereby the locking means 6 are formed by an upward directed portion 53 at the tongue 9 which, as a result of a turning movement, is brought behind a downward-directed portion 54 at the upper wall 18. More particularly, this is obtained by realizing the upper side 17 and the upper wall 18 with a curvature R3, the center of which is situated at the edges 15-16, and realizing the lower side 12 and the lower wall 14 with a radius R4, the center of which is also situated at the upper edges 15 and 16, respectively. These radii R3-R4 can be chosen otherwise, too.

[0066] In general, according to the invention, the difference between, on one hand, the radius R1, R3 respectively, and, on the other hand, the radius R2, R4 respectively, preferably should not be larger than 2 mm.

[0067] It is also preferred that the center of these radii is situated inside the circle C1, C2 respectively, which extends with a radius R5 of 3 mm around the upper edge 15, 16 respectively, such as, for example, indicated in figure 2.

[0068] Finally is noted that, according to the invention, the lower lip 23-43, as represented in figures 2 to 7, can be realized longer than the upper lip 22-42. This has as an advantage that the coupling parts 4-5-28-29 can be realized in an easier manner by means of a milling cutter or such. Furthermore, this simplifies the engagement of two floor panels 1, because each subsequent floor panel

1 during installation can be placed upon the protruding lower lip 23-43, as a result of which the tongue 9-31 and the groove 10-32 automatically are positioned in front of each other.

[0069] The embodiments whereby the lower lip 23 is equal to or shorter than the upper lip 22, in their turn, offer the advantage that no protruding lip 23 remains at the extreme edge of the floor which might cause problems in the finishing.

[0070] In order to allow for a smooth assembly, in order to guarantee the necessary stability and firmness and in order to limit the quantity of material to be cut away, the difference E between the upper lip 22-42 and the lower lip 23-43, measured in the plane of the floor panel and perpendicular to the longitudinal direction of the groove 10, should preferably be kept smaller than one time the total thickness F of the floor panel 1. For stability's sake, normally this total thickness F shall never be less than 5 mm.

[0071] The small dimension of the difference E offers the advantage that the lower lip must not be strengthened by a reinforcement strip or the like.

[0072] According to a particular form of embodiment, the central line M1 through the tongue 9 and the groove 10 is situated lower than the center M2 of the floor panel 1, such, that the upper lip 22-42 is thicker than the lower lip 23-43. In first instance, this is essential in this kind of connections, because then it is the lower lip 23-43 which bends, such that the upper side of the floor panel 1 is kept free of possible deformations.

[0073] As explained in the introduction, for the core 8 a material is chosen from the following series:

- a ground product which, by means of a binding agent or by means of melting together, is composed to a single compound;
- a product based on synthetic material;
- chip board with fine chips.

[0074] The invention shows its usefulness, in first instance, preferably with laminated flooring, due to the reasons explained in the introduction.

[0075] As represented in the examples of the figures 2 to 11, such laminated flooring preferably consists of a core 8 made of MDF board, HDF board or similar, whereby at least at the upper side of this core 8 one or more layers of material are provided.

[0076] More particularly, it is preferred that the laminated flooring is provided with a decorative layer 55 and a protective top layer 56. The decorative layer 55 is a layer, impregnated with resin, for example, made of paper, which can be imprinted with a variety of patterns, such as a wood pattern, a pattern in the form of stone, cork, or similar or even with a fancy pattern. The protective top layer 56 preferably also consists of a layer saturated with resin, for example, melamine resin, made of a transparent material.

[0077] It is clear that still other layers can be applied,

such as an intermediate layer 57 upon which the decorative layer 55 is provided.

[0078] Preferably, also a backing layer 58 shall be applied at the underside 7, forming a counterbalancing element for the top layers and, thus, guaranteeing the stability of the form of the floor panel 1. This backing layer 58 may consist of a material, for example paper, impregnated with a resin, for example, a melamine resin.

[0079] As represented schematically in figure 12, the tongue 9 and the groove 10, and preferably also the tongue 31 and the groove 32 are applied by means of a milling process. In the case that a profile has to be applied on all four sides, the floor panels 1 preferably shall be displaced by means of two perpendicular movements V1 and V2, whereby during the first movement profiles at two opposite edges are provided, in this case the longitudinal edges, by means of milling devices 59-60, whereas during the second movement profiles are provided at the other edges, in this case the small edges, by means of milling devices 61-62. During these processing, the floor panels 1 preferably are put with their decorative layer directed downward.

[0080] According to an important characteristic of the invention, each respective tongue 9-31 and groove 10-32 are realized by means of a milling process with at least two subsequent milling cycles by means of milling cutters which are positioned at different angles in reference to the related floor panel 1.

[0081] This is illustrated in figures 13, 14 and 15, wherein it is represented how a groove 10 is realized by means of two milling cycles by means of two milling cutters 63 and 64. Figures 16 and 17 represent how the tongue 9 is realized by means of milling cutters 65 and 66.

[0082] The figures 18-19 and 20-21 represent similar views showing how the groove 32 and the tongue 31 are realized by means of milling cutters 67-68 and 69-70, positioned at an angle.

[0083] During each of the aforementioned milling cycles, each time substantially the final shape of one flank is realized. For example, the milling cutter 63 of figure 14 determines the final shape of the lower flank 71 of the groove 10, whereas the milling cutter 64 determines the final shape of the upper flank 72.

[0084] As mentioned in the introduction, preferably milling cutters 63 to 72 shall be applied, having diameters G which are at least 5 times, and even better at least 20 times larger than the thickness F of the floor panels 1.

[0085] Apart of the mentioned milling cutters, preferably still other milling cutters are applied, for example, in order to remove a part of the material to be removed already during a first premachining cycle.

[0086] In the figures 22 to 25, a particularly preferred form of embodiment of a floor panel 1 according to the invention is represented. Hereby, the parts which are taken over from the foregoing forms of embodiment are indicated with corresponding references.

[0087] An important characteristic herein consists in

that the coupling parts 4-5 are provided with locking means 6 which, in engaged condition, exert a tension force upon each other, as a result of which the engaged floor portions 1 are forced towards each other. As represented, this is realized preferably by providing the coupling parts with an elastically bendable portion, in this case the lip 43, which, in engaged condition, is at least partially bent and in this way creates a tension force which provides for that the engaged floor panels 1 are forced towards each other. The hereby resulting bending V, as well as the tension force K resulting herefrom, are indicated in the enlargement of figure 23.

[0088] In order to obtain that the tension force K results in pressing together the engaged floor panels 1, the bendable portion, in this case the lip 43, preferably is provided, as represented, with an inwardly inclined contact surface 73 which preferably can cooperate with a corresponding contact surface 74. These contact surfaces 73-74 are similar to the aforementioned contact surfaces 39-38 and also similar to the inclined portions of the lower lip of figures 2 to 4.

[0089] In the figures 2 and 5, the portions form complementary matching shapes; it is, however, clear that, by a modification, also a tension effect similar as in figure 23 can be realized.

[0090] Due to, on one hand, the contact under the angle A, and, on the other hand, the fact that a tension force K is created, a force component K1 is effected, as a result of which the floor panels 1 are drawn against each other.

[0091] Preferably, the angle A of the contact surfaces 73-74 in respect to the horizontal plane is situated between 30 and 70 degrees. In first instance in the case that use is made of the embodiment whereby a tension force K is realized, an angle A of 30 to 70 degrees is ideal in order, on one hand, to effect an optimum pressing-together of the floor panels 1 and, on the other hand, to obtain that the floor panels 1 can easily be engaged, respectively disassembled.

[0092] Although the pressing force K1 preferably is delivered by the aforementioned lip 43, the invention does not exclude other forms of embodiment whereby this force is delivered by other bendable portions.

[0093] It is noted that the bending V is relatively small, for example, several hundredths up to several tenths of a millimeter, and does not have an influence upon the placement of the floor covering. Furthermore is noted that such floor covering generally is placed upon an underlayer which is elastically compressible, as a result of which the bending V of the lip 43 exclusively results in the fact that the underlayer locally is compressed somewhat more.

[0094] Due to the fact that the lip 43 is bent apart and that it remains somewhat bent apart in engaged position, also the advantage is effected that, when exerting a pressure upon the floor covering, for example, when placing an object thereupon, the pressing-together force is enhanced and, thus, the development of gaps is coun-

teracted even more.

[0095] It is noted that the inventor has found that, contrary to all expectations, an ideal tension force can be realized by manufacturing the coupling parts 4-5, including the locking elements 33-34, and preferably the complete core 8, of HDF board or MDF board, although these materials only allow a minor elastic deformation.

[0096] HDF and MDF also offer the advantage that smooth surfaces are obtained, as a result of which the locking elements can be moved easily over each other.

[0097] According to a variant of the invention, the tension force can also be delivered by means of an elastic compression of the material of the coupling parts, to which end these coupling parts, and preferably the complete core 8, then have to be manufactured in an elastically compressible material.

[0098] A further particular characteristic of the embodiment of figures 22 to 25 consists in that the floor panels 1 can be engaged by means of a turning movement, as represented in figure 24, as well as by means of shifting them towards each other, as represented in figure 25, preferably in such a manner that, during the engagement by means of the turning movement, a maximum bending Vm results in the coupling parts, more particularly in the lip 43, which bending Vm is less pronounced, if not non-existent, as in the figures 2 to 4, in comparison to the bending Vm which results when the floor panels 1 are engaged by means of shifting them towards each other.

[0099] The advantage of this consists in that the floor panels 1 can be engaged easily by means of a turning movement, without necessitating a tool therefore, whereas it still remains possible to engage the floor panels also by means of shifting them. This latter is useful, in first instance, when the last panel has to be placed partially under a door frame or similar. In this case, the floor panel 1 can be pushed under the door frame with the side which does not have to be engaged and subsequently, possibly by means of tools, can be snapped into the adjacent floor panel 1.

[0100] It is noted that the shapes of the coupling parts 4-5 shown in figures 22 to 25 can also be used for the coupling parts 28-29 of the short sides.

[0101] According to the invention, in the case that the four sides 2-3-26-27 are provided with coupling parts 4-5-28-29, these coupling parts can be realized in such a manner that in one direction a firmer engagement than in the other direction is effected. In the case of elongated floor panels 1, for example, such as represented in figure 1, the locking at the small sides 26-27 preferably shall be more pronounced than at the longitudinal sides 2-3. The length of the coupling at the small sides, namely, is smaller and, in principle, less firm. This is compensated by providing in a more pronounced locking.

[0102] This difference in engagement can be obtained by realizing the contact surfaces 73-74 under different angles.

[0103] Preferably, the aforementioned protrusion,



more particularly the locking element 33, is bordered by at least two portions 75-76, respectively a portion 75 with a strong inclination which provides for the locking, and a portion 76 with a weaker inclination which renders the engagement of the coupling parts easier. In the embodiment of figures 22 to 25, these portions 75-76 are formed by straight planes, but, as already described in reference to figure 9, use can also be made of curved portions 50-51. In figure 5, these are the contact surface 38 and the inclined portion 40.

[0104] In the preferred form of embodiment, the floor panels 1 according to the invention comprise coupling parts 4-5 and/or 28-29 showing one of the following or the combination of two or more of the following features:

- a curvature 77 at the lower side of the tongue 9 and/or a curvature 78 at the lip 43 which form a guidance when turning two floor panels 1 into each other, with the advantage that the floor panels 1 can be engaged into each other easily during installing;
- roundings 79-80 at the edges of the locking elements 33-34, with the advantages that the locking elements can easily shift over each other during the engagement, respectively disassembly of the floor panels 1 and that the locking elements are not damaged, for example, crumble away at their edges, even if the floor panels are engaged, respectively disassembled, repeatedly;
- dust chambers 81, or spaces 21 as in figure 4, between all sides, directed laterally towards each other, of the engaged floor panels 1, with the advantage that inclusions which get between the floor panels 1 during the engagement do not exert a disadvantageous influence upon the good engagement;
- a shaping of the tongue 9 which is such, for example, by the presence of a chamfer 82, that the upper side of the tongue 9 already with the first contact becomes situated under the lower side of the upper lip 42 when the floor panels 1 are pushed towards each other at the same level, as indicated in figure 25, with the advantage that the front extremity of the tongue 9 does not press against the front side of the upper lip 42 when the floor panels are pushed towards each other at the same level;
- a ramp surface 83, hereinbefore also called inclined portion 41, formed at the free extremity of the lower lip 43, with the advantage that the locking elements 33-34 shift smoothly over each other and that the lower lip 43 is bent uniformly;
- in the engagement direction only one important contact point which is formed by a section 84 at the location of the top side of the floor panels 1, with the advantage that the aforementioned tension force is optimally transferred to the upper side of the floor panels 1 and that the development of openings between the floor panels 1 is counteracted;
- contact surfaces 85-86, more particularly abutment

surfaces, formed by the upper side of the tongue 9 and the upper side of the groove 10 which, over the largest portion of their length, run parallel to the plane which is defined by the floor panels 1, as well as contact surfaces cooperating with each other, formed by curvatures 77-78, with the advantage that no mutual displacement in height between two engaged floor panels 1 is possible, even if the insertion depth of the tongue 9 into the groove 10 should vary due to which causes whatsoever, in other words, that no height differences may occur between the adjacent floor panels.

[0105] In the form of embodiment of figures 22 to 25, all these characteristics are combined; it is, however, clear that, as becomes evident from figures 2 to 11, these features can also be present separately or in a limited combination.

[0106] As becomes evident from figures 5 to 7 and 22 to 25, an important characteristic of the preferred form of embodiment of the invention consists in that the locking means 6, in other words, the portion providing for the snap-together and engagement effect, are situated in that portion of the lower lip 23-43 which extends beyond the upper lip 22-42, more particularly, that the lowermost point 87 of the locking part 33 is situated under the top layer of the floor panel 1. For clarity's sake, this top layer is indicated in the figures 22 to 25 only as a single layer.

[0107] It is noted that the combination of features, that the lower lip 23-43 extends further than the upper lip 22-42, that the locking means 6 are formed at least by means of a portion which inwardly slopes downward, and that this portion, at least partially, is located in the portion of the lower lip 23-43 which extends beyond the upper lip 22-42, is particularly advantageous, among others, in comparison with the couplings for floor panels described in the documents WO 94/01628, WO 94/26999, WO 96/27719 and WO 96/27721. The sloping portion offers the advantage that the floor panels 1 can be disassembled again. The fact that this sloping portion is situated in the further extending portion of the lower lip 23-43 additionally to this offers the advantage that no deformations can occur during coupling which manifest themselves up to the top layer.

[0108] According to a preferred characteristic of the invention, the aforementioned portion, i.e. the contact surface 39 or 73, preferably extends in such a manner that the distance up to the upper edge 16 diminishes from below in upward direction, in other words, such that, as represented in figure 22, the distance X2 is smaller than the distance X1. This is also the case in figure 7.

[0109] Still preferably, this portion only starts at a clear distance E1 from the upper lip 42.

[0110] It is obvious that the coupling parts 22 to 25 can also be realized by means of said milling process.

[0111] According to a particular characteristic of the



invention, the floor panels 1 are treated at their sides 2-3 and/or 26-27 with a surface densifying agent, more particularly a surface hardening agent, which preferably is chosen from the following series of products: impregnation agents, pore-sealing agents, lacquers, resins, oils, paraffines and similar.

[0112] In figure 22, such impregnation 88 is represented schematically. This treatment can be performed over the complete surface of the sides 2-3 and/or 26-27 or only over well-defined portions hereof, for example, exclusively the surfaces of the tongue 9 and the groove 10.

[0113] The treatment with a surface densifying agent offers, in combination with the snap-together effect, the advantage that in various aspects better coupling features are obtained. As a result of this, the coupling parts 4-5 and/or 28-29 better keep their shape and strength, even if the floor panels 1 are engaged and disassembled repeatedly. Especially in the case that for the core 8 use is made of HDF, MDF or similar, by means of this treatment such a better quality of surface condition is obtained, that no abrasion of material occurs during engaging, respectively during disassembling.

[0114] This treatment also offers the advantage that, at least in the case of a surface hardening, the aforementioned elastic tensioning effect is enhanced.

[0115] The present invention is in no way limited to the forms of embodiment described by way of example and represented in the figures, however, can such floor covering and the pertaining floor panels 1 be realized in various forms and dimensions without leaving the scope of the invention.

[0116] For example, the various characteristics which are described by means of the represented forms of embodiment, may be combined with each other or not.

[0117] Furthermore, all embodiments of coupling elements described before can be applied at the longer side as well as at the shorter side.

## Claims

1. Floor covering, consisting of hard floor panels (1) which, at least at the edges of two opposite sides (2-3, 26-27), are provided with coupling parts (4-5, 28-29), co-operating with each other, substantially in the form of a tongue (9-31) and a groove (10-32), whereby the coupling parts are provided with integrated mechanical locking means (6) made in one piece with the panels (1) which prevent the drifting apart of two coupled floor panels (1) into a direction (R) perpendicular to the related edges (2-3, 26-27) and parallel to the underside (7) of the coupled floor panels (1), characterized in that the coupling parts (4-5, 28-29) are provided with means which, in the engaged condition of two or more of such floor panels (1), exert a tension force upon each other which forces the floor panels (1) towards each other, said means comprising an elastically bendable portion

which, in the engaged condition, is at least partially bent, and in this manner provides the aforementioned tension force.

2. Floor covering according to claim 1, characterized in that in the engagement direction, apart from a contact formed by contact surfaces (38-39, 73-74) delivering the tension force, there exists only one substantial contact point between two coupled floor panels (1), which is formed by a section (84) at the location of the top side of the floor panels (1).
3. Floor covering according to claim 1 or 2, characterized in that the elastically bendable portion consists of a lip, preferably the lip (23-43) limiting the lower side of the aforementioned groove (10).
4. Floor covering according to claim 3, characterized in that the bendable portion which is bent out in coupled condition is formed by the lower lip (23-43) of said groove (10-32) whereby this lip (23-43) in coupled condition is bent out only downwardly.
5. Floor covering according to claim 3 or 4, characterized in that the bendable portion is provided with a contact surface (39-73) which inwardly slopes downward.
6. Floor covering according to claim 5, characterized in that said contact surface (39-73) co-operates with a corresponding contact surface (38-74) and in that said co-operating contact surfaces define a tangent line (L) which forms an angle (A) with the underside (7) of the floor panels (1) which is 30° to 70°.
7. Floor covering according to any of the claims 3 to 6, characterized in that the locking means (6) comprise, at a first edge (2-27), a recess (13-36) in said lip, more, particularly in said lower lip (23-43), and at a second edge (3-26), opposite to the first edge, a protrusion which in coupled condition of two panels (1) co-operates with the recess of the other panel, said recess and protrusion defining contact surfaces (38-39, 73-74) the contact of which results in said tension force.
8. Floor covering according to claim 7, characterized in that the thickness of the lower lip (23-43) increases from the deepest point of the recess towards the innermost point of the groove (10-32).
9. Floor covering according to claim 7 or 8, characterized in that the tongue (9-31) and groove (10-32) have a shape such that in coupled condition of two floor panels (1) there exists a chamber (81) between those sides of the protrusion and the recess (36) that are located opposite to the sides at which the contact surfaces (39-73) are formed.

bestehend aus dem biegsamen Teil

10. Floor covering according to any of claims 7 to 9, characterized in that the coupling parts (4-5) show one of the following or the combination of two or more of the following features:

- roundings (79-80) at the edges of the locking elements (33-34);
- dust chambers or similar (21-44-81) between all sides of the engaged floor panels (1) which are directed laterally towards each other;
- a ramp surface (41-83), formed at the free extremity of the lower lip (43);
- contact surfaces (85-86), more particularly abutment surfaces, formed by the upper side of the tongue (9) and the upper side of the groove (10) which, over the largest portion of their length, run parallel to the plane which is defined by the floor panels (1).

11. Floor covering according to any of the preceding claims, characterized in that the groove is bordered by an upper lip and a lower lip and that the lip (23-43) bordering the lower side of the groove (11-32) extends beyond the lip (22-42) bordering the upper side of the groove (10-32).

12. Floor covering according to claim 11, characterized in that lower lip extends beyond the upper lip, whereby the difference (E) between the lips measured in the plane of the floor panel is smaller than one time the total thickness (F) of the floor panel (1).

13. Floor covering according to any of the preceding claims, characterized in that the locking means (6) comprise locking elements (13-34) which are located in the portion of the lower lip (23-43) which extends beyond the upper lip (22-42).

14. Floor covering according to any of the preceding claims, characterized in that the coupling parts (4-5, 28-29) have such a shape that two subsequent floor panels (1) can be engaged into each other by shifting them laterally together as well as by turning, thereby in particular allowing a snapping together action.

15. Floor covering according to any of the preceding claims, characterized in that the groove is bordered by an upper lip and a lower lip and in that the lower lip (23-43) has a thickness which is smaller than the thickness of the upper lip (22-42).

16. Floor covering according to any of the preceding claims, characterized in that the panels (1) have a core made of HDF board or MDF board, whereby said coupling means, inclusive said bendable portion, are substantially formed out of said board such that the tension force is delivered by the elasticity

of the HDF or MDF.

17. Floor covering according to any of the preceding claims, characterized in that the panels (1) are rectangular; in that the panels (1) are provided with coupling parts and locking means (6) at both pairs of opposite edges; and in that the means providing in the tension force are integrated at both pairs of edges such that the panels (1) in engaged condition are forced to each other at all coupled edges.

18. Floor covering according to any of the preceding claims, characterized in that the panels (1) at least at two opposite edges are provided of coupling parts which allow to couple the panels (1) at these edges at least by rotation, whereby as the result of the angling down of the panels (1) the elastically bendable portion is bent; and in that the panels (1) at least at the two other opposite edges are provided with coupling parts which allow to couple the panels (1) at these edges at least by shifting, whereby as the result of this shifting also the elastically bendable portion at these edges remains in a bent condition.

19. Floor covering according to any of the preceding claims, characterized in that the floor panels (1) are realized as laminated flooring, whereby on the core (8) one or more layers, among which a decorative layer (55) forming said decorative surface, are provided and whereby a backing layer (58) is provided at the underside (7).

20. Floor covering according to any of the preceding claims, characterized in that the floor panels (1) are connected free of glue, such that they can be disassembled and be re-used.

21. Floor panel for realizing a floor covering according to any of the claims 1 to 20.

22. A method of assembling a floor covering, characterized in that said floor covering consists of hard floor panels (1) of rectangular shape which, at least at two opposite sides (2-3, 26-27), are provided with coupling parts (4-5, 28-29) cooperating with each other, substantially in the form of a tongue (9-31) and a groove (10-32), whereby the coupling parts (4-5, 28-29) are provided with integrated mechanical locking means (6), made in one piece with the panels (1), which prevent the drifting apart of two coupled floor panels (1) into a direction (R) perpendicular to the related edges (2-3, 26-27) and parallel to the underside (7) of the coupled floor panels (1), whereby the lower lip (23-43) which limits the lower side of the groove (10), extends beyond the upper lip (22-42) and whereby said locking means (6) comprise a portion which inwardly slopes down-

ward, which portion, at least partially, is located in the portion of the lower lip (23-43) which extends beyond the upper lip (22-42), whereby this portion cooperates with a surface at the lower side of the tongue, which is also inclined, and in that said method comprises the steps of:

- laying a first of said hard floor panels (1); and
- coupling a second panel to said first panel, by fitting the tongue and groove into each other, thereby providing that the lower lip is bent out in coupled condition, such that said lip, by means of the inclined portions provides in a force by which the panels (1) are permanently urged towards each other.

23. A method according to claim 22, characterized in that the second panel is coupled to the first panel by fitting the tongue and groove into each other, in a position whereby the second panel is angled upwards in respect to the first panel, and subsequently by angling down the second panel, thereby ending up in a position whereby both panels (1) are coplanar in respect to each other, whereby the lower lip of the first panel is urged downwards over a distance (V).

24. A method according to claim 22, characterized in that the second panel is coupled to the first panel by fitting the tongue and groove into each other, whereby this is obtained by shifting the second panel to the first panel in a substantially planar fashion, thereby ending up in a position whereby both panels (1) are coplanar and in coupled condition, whereby the lower lip of the first panel remains urged downwards over a distance (V) after the shifting.

25. Method according to claim 22, characterized in that floor panels (1) are applied which are provided with said coupling parts and locking means at both pairs of opposite sides (2-3, 26-27) and in that the method comprises the steps of:

- laying a first of said floor panels (1);
- coupling a second panel to said first panel, by fitting the tongue and groove into each other, thereby providing in that the lower lip is bent out in coupled condition, such that said lip, by means of the inclined portions provides in a force by which the panels (1) are permanently urged towards each other; and
- coupling a third panel to the first as well as second panel, respectively at a first edge and a second edge perpendicular to the first edge, thereby providing in that the lower lip at both edges is bent out in coupled condition, such that each of said lips, by means of the inclined portions provides in a force by which the panels

(1) are permanently urged towards each other.

26. Method according to claim 25, characterized in that the pretension at both edges is built up by respectively the steps of:

- coupling the third panel to the first panel by fitting the tongue and groove of the third and first panel into each other, in a position whereby the third panel is angled upwards in respect to the first panel, and subsequently by angling down the third panel, thereby ending up in a position whereby both panels (1) are coplanar in respect to each other, whereby the lower lip of the first panel is urged downwards over a small distance (V); and
- coupling the third panel to the second panel by fitting the tongue and groove of the respective panels (1) into each other, whereby this is obtained by shifting the third panel to the second panel in a substantially planar fashion, thereby ending up in a position whereby both panels (1) are coplanar and in coupled condition, whereby the lower lip of the second panel remains urged downwards over a small distance (V).

27. Method according to claim 25, characterized in that the pretension at both edges is built up by respectively the steps of:

- coupling the third panel to the first panel by fitting the tongue and groove of the respective panels (1) into each other, whereby this is obtained by shifting the third panel to the first panel in a substantially planar fashion, thereby ending up in a position whereby both panels (1) are coplanar and in coupled condition, whereby the lower lip of the first panel remains urged downwards over a small distance (V); and
- coupling the third panel to the second panel by fitting the tongue and groove of the respective panels (1) into each other, whereby this is obtained by shifting the third panel to the second panel in a substantially planar fashion, thereby ending up in a position whereby both panels (1) are coplanar and in coupled condition, whereby the lower lip of the second panel also remains urged downwards over a small distance (V).



28. A method according to any of the claims 22 to 27, characterized in that the panels (1) are installed on a flexible underlay, whereby the elastically bent portions of the panels (1) which provide in that the panels (1) are pressed to each other, are bent out downwards and whereby the unevenness caused by these portions is taken up by the flexibility of the underlay.

29. Floor panel for realizing a floor covering, characterized in that said floor panel is provided at its edges with coupling parts (4-5,28-29) and locking means (6) allowing that a plurality of such floor panels (1) can be assembled according to the method of any of claims 25 to 28. 5
30. Method for manufacturing floor panels according to claim 21 or 29, characterized in that the tongue (9-31) and/or groove (10-32) is realized by means of a milling process with at least two subsequent milling cycles by means of milling cutters (63-64-65-66-67-68-69-70) which are positioned in different angles in respect to the related floor panel (1). 10 15
31. Method according to claim 30, characterized in that during each of the aforementioned milling cycles each time substantially the final shape of one flank (71-72), either of the tongue or to the groove, is realized. 20
32. Method according to claim 30 or 31, characterized in that for the aforementioned two milling cycles milling cutters (63-64-65-66-67-68-69-70) are applied which extend outside the groove (10-32), respectively the tongue (9-31), and more particularly show diameters (G) which are at least 5 times larger than the thickness (F) of the floor panels (1), and preferably even at least 20 times larger than the thickness (F) of the floor panels (1). 25 30
33. Method according to any of the claims 30 to 32, characterized in that at all four sides of the floor panel (1) a profile is provided and that the floor panels (1) are displaced according to two perpendicular movements (V1-V2), whereby during one of the movements profiles at two opposite edges are provided, whereas during the other movement profiles are provided at the small edges. 35 40

45

50

55






Fig. 2




Fig. 3












Fig. 4













*Fig. 14*





*Fig. 15*




*Fig. 16*


*Fig. 17*




*Fig. 18*



*Fig. 19*





*Fig.20*



*Fig.21*







**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**